


IGBT Discrete

V_{CE}	1200	V
I_C	50	A
$V_{CE(SAT)} I_C=50A$	1.55	V

Circuit



Applications

- Frequency Converters
- AC and DC servo drive amplifier
- Uninterruptible power supply

Features

- High breakdown voltage to 1200V for improved reliability
- Maximum junction temperature 175°C
- Positive temperature coefficient
- Including fast & soft recovery anti-parallel FWD
- High short circuit capability(10us)

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Breakdown Voltage	V_{CE}	1200	V
DC Collector Current, limited by T_{jmax} $T_C=25^\circ C$ $T_C=100^\circ C$	I_C	80 50	A
Diode Forward Current, limited by T_{jmax} $T_C=25^\circ C$ $T_C=100^\circ C$	I_F	80 50	A
Continuous Gate-Emitter Voltage	V_{GE}	± 20	V
Transient Gate-Emitter Voltage ($t_p \leq 10\mu s, D < 0.010$)	V_{GE}	± 30	V
Turn off Safe Operating Area $V_{CE} \leq 1200V$, $T_j \leq 150^\circ C$		150	A
Pulsed Collector Current, $V_{GE}=15V$, t_p limited by T_{jmax}	I_{CM}	150	A
Diode Pulsed Current, t_p limited by T_{jmax}	I_{Fpuls}	150	A
Short Circuit Withstand Time, $V_{GE}=15V, V_{CC}=600V, V_{CEM} \leq 1200V$	T_{sc}	10	μs
Power Dissipation, $T_j=175^\circ C, T_C=25^\circ C$	P_{tot}	468	W

Operating Junction Temperature	T_j	-40...+175	°C
Storage Temperature	T_s	-55...+150	°C
Soldering Temperature, wave soldering 1.6mm (0.063in.) from case for 10s		260	°C

Electrical Characteristics of the IGBT ($T_j = 25^\circ\text{C}$ unless otherwise specified):

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Collector-Emitter Breakdown Voltage	BV_{CES}	$V_{GE}=0V, I_C=250\mu A$	1200		-	V
Gate Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=1mA$	5.0	5.6	6.2	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=50A$ $T_j=25^\circ\text{C}$ $T_j=125^\circ\text{C}$ $T_j=150^\circ\text{C}$		1.55 1.85 1.95	1.85	V
Zero Gate Voltage Collector Current	I_{CES}	$V_{CE}=1200V, V_{GE}=0V$ $T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$			0.25 4	mA
Gate-Emitter Leakage Current	I_{GES}	$V_{CE}=0V, V_{GE}=\pm 20V$			100	nA

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic						
Input Capacitance	C_{ies}	$V_{CE}=25V, V_{GE}=0V,$ $f=1MHz$	-	6.73	-	nF
Reverse Transfer Capacitance	C_{res}		-	0.09	-	
Gate Charge	Q_G	$V_{CC}=600V, I_C=50A,$ $V_{GE}=15V$	-	0.34	-	uC

Electrical Characteristics of the Diode (T_j= 25°C unless otherwise specified):

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Diode Forward Voltage	V _F	I _F = 50A T _j = 25°C, T _j = 125°C T _j = 150°C		2.00 1.85 1.75	2.60	V

Switching Characteristic, Inductive Load





Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T _j = 25℃						
Turn-on Delay Time	t _{d(on)}	V _{CC} = 600V, I _C =50A, V _{GE} = -5V~15V, R _g =10Ω	-	53	-	ns
Rise Time	t _r		-	74	-	ns
Turn-on Energy	E _{on}		-	4.02	-	mJ
Turn-off Delay Time	t _{d(off)}		-	221	-	ns
Fall Time	t _f		-	178	-	ns
Turn-off Energy	E _{off}		-	2.66	-	mJ
Dynamic , at T _j = 125℃						
Turn-on Delay Time	t _{d(on)}	V _{CC} = 600V, I _C =50A, V _{GE} = -5V~15V, R _g =10Ω	-	51	-	ns
Rise Time	t _r		-	75	-	ns
Turn-on Energy	E _{on}		-	4.43	-	mJ
Turn-off Delay Time	t _{d(off)}		-	212	-	ns
Fall Time	t _f		-	231	-	ns
Turn-off Energy	E _{off}		-	2.99	-	mJ
Dynamic , at T _j = 150℃						
Turn-on Delay Time	t _{d(on)}	V _{CC} = 600V, I _C =50A, V _{GE} = -5V~15V, R _g =10Ω	-	50	-	ns
Rise Time	t _r		-	76	-	ns
Turn-on Energy	E _{on}		-	4.64	-	mJ
Turn-off Delay Time	t _{d(off)}		-	194	-	ns
Fall Time	t _f		-	256	-	ns
Turn-off Energy	E _{off}		-	3.14	-	mJ





Electrical Characteristics of the DIODE





Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T _j = 25°C						
Reverse Recovery Current	I _{rr}	I _F =50A, V _R =600V, di/dt= -500A/μs,	-	15	-	A
Diode reverse recovery time	trr		-	255	-	ns
Reverse Recovery Charge	Q _{rr}		-	1.48	-	uC
Reverse Recovery Energy	E _{rec}		-	0.42	-	mJ
Dynamic , at T _j = 125°C						
Reverse Recovery Current	I _{rr}	I _F =50A, V _R =600V, di/dt= -500A/μs,	-	17	-	A
Diode reverse recovery time	trr		-	323	-	ns
Reverse Recovery Charge	Q _{rr}		-	3.74	-	uC
Reverse Recovery Energy	E _{rec}		-	1.09	-	mJ
Dynamic , at T _j = 150°C						
Reverse Recovery Current	I _{rr}	I _F =50A, V _R =600V, di/dt= -500A/μs,	-	18	-	A
Diode reverse recovery time	trr		-	367	-	ns
Reverse Recovery Charge	Q _{rr}		-	4.51	-	uC
Reverse Recovery Energy	E _{rec}		-	1.45	-	mJ





Thermal Resistance

Parameter	Symbol	Max. Value	Unit
IGBT Thermal Resistance, Junction - Case	R _{θ(j-c)}	0.32	K/W
Diode Thermal Resistance, Junction - Case	R _{θ(j-c)}	0.65	K/W
Thermal Resistance, Junction - Ambient	R _{θ(j-a)}	40	K/W












Fig 17. Diode Transient Thermal Impedance




Fig18. Diode forward current as a function of forward voltage





Fig19. Diode forward voltage as a function of junction temperature

● Circuit Diagram



● Package Outline Information



TO-247AB		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.0	1.4
b2	1.91	2.21
C	0.5	0.7
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.0	13.6
E2	4.80	5.20
E3	2.30	2.70
L	19.62	20.22
L1	-	4.30
Φ P	3.40	3.80
Φ P1	-	7.30
S	6.15TYP	
H1	5.44TYP	
b3	2.80	3.20

Disclaimer

The information presented in this document is for reference only. This publication is made by Shanghai Sunco Electronics Co., Ltd. , our company reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The data provided in this specification comes from professional testing equipment of Russiansunco Electronic Laboratory, not general testing equipment. All the data is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

IGBTs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.