



Low VF Bridge Rectifiers



Features

- UL recognition, file #E230084
- Glass passivated chip junction
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package:** 6KBJ
Molding compound meets UL 94 V-0 flammability rating, -
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	GBJL2508A
Device marking code				GBJL2508A
Maximum Repetitive Peak Reverse Voltage		VRRM	V	800
Maximum RMS Voltage		VRMS	V	560
Maximum DC blocking Voltage		VDC	V	800
Average rectified output current @60Hz sine wave, R-load	With heatsink T _C =104℃	I _O	A	25.0
	Without heatsink T _A =25℃			3.5
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, T _J =25℃		I _{FSM}	A	450
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, T _J =25℃				900
Current squared time @1ms≤t≤8.3ms T _J =25℃, Rating of per diode		I ² t	A ² s	840
Storage temperature		T _{stg}	℃	-55 ~ +150
Junction temperature		T _j	℃	-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute		V _{dis}	KV	2.5
Mounting torque @Recommend torque: 5kg·cm		Tor	kg·cm	8

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	GBJL2508A
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =12.5A	0.92
Maximum DC reverse current at rated DC blocking voltage per diode	I _R	μA	T _j =25°C	5
			T _j =125°C	200
Typical junction capacitance	C _j	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	275

GBJL2508A

■ Thermal Characteristics (T_a=25°C Unless otherwise specified)





PARAMETER		SYMBOL	UNIT	GBJL2508A
Typical Thermal Resistance	Between junction and ambient, Without heatsink	R _{θJ-A}	°C/W	18.0
	Between junction and case, With heatsink	R _{θJ-C}		1.0

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.


■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GBJL2508A	B1	Approximate 6.5	15	750	1500	TUBE

■ Characteristics(Typical)



■ Outline Dimensions



6KBJ		
Dim	Min	Max
A	29.7	30.3
B	19.7	20.3
C	17.0	18.0
D	4.8	5.8
E	3.8	4.2
F	7.3	7.7
G	9.8	10.2
H	0.9	1.1
I	2.0	2.4
J	2.3	2.7
K	3.4	3.8
L	4.4	4.8
M	10.8	11.2
N	3.1	3.7
O	3.1	3.4
P	0.6	0.8

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.