


Surface Mount General Purpose Rectifier



Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in general purpose rectification of power supplies, inverters, converters, and freewheeling diodes for consumer and telecommunication.

Mechanical Data

- **Package:** DO-214AC (SMA)
Molding compound meets UL 94 V-0 flammability rating, -compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GS1AL	GS1BL	GS1DL	GS1GL	GS1JL	GS1KL	GS1ML
Device marking code			GS1AL	GS1BL	GS1DL	GS1GL	GS1JL	GS1KL	GS1ML
Maximum Repetitive Peak Reverse Voltage	VRRM	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	VRMS	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	VDC	V	50	100	200	400	600	800	1000
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I _O	A	1.0						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, T _j =25°C	I _{FSM}	A	35						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, T _j =25°C			62						
Current squared time @1ms≤t≤8.3ms T _j =25°C	I ² t	A ² s	5.083						
Storage temperature	T _{stg}	°C	-55 ~ +150						
Junction temperature	T _j	°C	-55 ~ +150						

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MIN	TYP	MAX
Reverse recovery time	TRR	ns	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	500	-	1000
Maximum instantaneous forward voltage	V _F	V	I _{FM} =1.0A	-	-	1.1
Maximum DC reverse current at rated DC blocking voltage	I _R	μA	T _j =25°C	-	-	5
			T _j =125°C	-	-	100
Typical junction capacitance	C _j	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	7.5		

GS1AL THRU GS1ML

■ Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GS1AL	GS1BL	GS1DL	GS1GL	GS1JL	GS1KL	GS1ML
Typical Thermal Resistance	R _{θJ-A} (1)	°C/W	85						
	R _{θJ-L} (1)	°C/W	33						
	R _{θJ-C} (1)	°C/W	20						

Note

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

■ Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GS1AL- GS1ML	F1	Approximate 0.059	5000	/	80000	13" reel
GS1AL- GS1ML	F2	Approximate 0.059	7500	/	120000	13" reel
GS1AL- GS1ML	F3	Approximate 0.059	7500	/	60000	13" reel
GS1AL- GS1ML	F4	Approximate 0.059	1800	14400	57600	7" reel
GS1AL- GS1ML	F5	Approximate 0.059	2000	16000	64000	7" reel
GS1AL- GS1ML	F6	Approximate 0.059	5000	/	100000	13" reel

■ Characteristics (Typical)

FIG.1: I_o-T_L Curve




FIG.2: Forward Surge Current Capability




FIG.3: Typical Forward Voltage






FIG.4: Typical Reverse Characteristics




■ Outline Dimensions



DO-214AC(SMA)		
Dim	Min	Max
A	1.25	1.58
B	2.40	2.83
C	4.00	4.75
D	1.90	2.30
E	4.93	5.28
F	0.76	1.41
G	0.05	0.20
H	0.15	0.31
I	1.70	2.10

■ Suggested Pad Layout



DO-214AC(SMA)	
Dim	Millimeters
P1	4.00
P2	1.50
P3	6.50
Q1	2.50
Q2	1.70

Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.