


MMBTA55 THRU MMBTA56

PNP General Purpose Amplifier



Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture Sensitivity Level 1
- High Conductance
- Surface Mount Package Ideally Suited for Automatic Insertion

Mechanical Data

- **Package:** SOT-23
Molding compound meets UL 94 V-0 flammability rating, -compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:**

MMBTA55	2H
MMBTA56	2GM

■Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Rating	Unit
Collector-Base Voltage	V_{CBO} MMBTA55 MMBTA56	-60 -80	V
Collector-Emitter Voltage	V_{CEO} MMBTA55 MMBTA56	-60 -80	V
Emitter-Base Voltage	V_{EBO}	-4	V
Collector Current	I_C	-500	mA
Collector Power Dissipation	P_C	300	mW
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	417	°C/W
Operation Junction Temperature	T_j	-55 to +150	°C
Storage Temperature	T_{stg}	-55 to +150	°C

MMBTA55 THRU MMBTA56

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Max
Collector-emitter breakdown voltage	V _{CEO}	V	I _C = -1mA, I _B = 0 MMBTA55 MMBTA56	-60 -80	
Emitter-base breakdown voltage	V _{EBO}	V	I _E = -100μA, I _C = 0	-4	
Collector-base cut-off current	I _{CBO}	μA	V _{CB} = -60V, I _E = 0, MMBTA55 V _{CB} = -80V, I _E = 0, MMBTA56		-0.1 -0.1
Collector-emitter cut-off current	I _{CES}	μA	V _{CE} = -60V, I _B = 0V,		-0.1
DC current gain	h _{FE}		V _{CE} = -1V, I _C = -10mA	100	400
	h _{FE}		V _{CE} = -1V, I _C = -100mA	100	
Collector-emitter saturation voltage	V _{CE(sat)}	V	I _C = -100mA, I _B = -10mA		-0.25
Base-emitter saturation voltage	V _{BE(sat)*}	V	I _C = -100mA, I _B = -10mA		-1.2



■Other Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Max
Transition frequency	f _T	MHz	V _{CE} = -1V, I _C = -100mA, f = 100MHz	50	

■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMBTA55 MMBTA56	F2	Approximate 0.009	3000	30000	120000	7" reel

■Characteristics(Typical)




MMBTA55 THRU MMBTA56


Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage



$C_{ob}/C_{ib}-V_{CB}/V_{EB}$






Collector Power Derating Curve




MMBTA55 THRU MMBTA56

■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

■SOT-23 Soldering Footprint



Disclaimer

The information presented in this document is for reference only. Shanghai Sunco Electronics Co., Ltd reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Russiansunco or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.russiansunco.com](http://www.russiansunco.com) , or consult your nearest Russiansunco's sales office for further assistance.